


## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>F41A 33/02</b>		<b>A1</b>	(11) International Publication Number: <b>WO 95/30124</b>
			(43) International Publication Date: 9 November 1995 (09.11.95)
(21) International Application Number: <b>PCT/US95/05253</b>		(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TT, UA, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ, UG).	
(22) International Filing Date: 28 April 1995 (28.04.95)			
(30) Priority Data: 08/237,717 29 April 1994 (29.04.94) US 08/415,595 3 April 1995 (03.04.95) US			
(71) Applicant: CUBIC DEFENSE SYSTEMS, INC. [US/US]; 9333 Balboa Avenue, San Diego, CA 92123-1589 (US).		<b>Published</b> <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	
(72) Inventors: PARIKH, Himnashu, N.; 4435 Nobel Drive #48, San Diego, CA 92122 (US). HEALEY, Fritz, W.; 930 Alyssum Road, Carlsbad, CA 92009 (US).			
(74) Agents: BAKER, Freling, E. et al.; Baker, Maxham, Jester & Meador, Suite 2770, 750 B Street, San Diego, CA 92101 (US).			

BEST AVAILABLE COPY

(54) Title: LASER SMALL ARMS TRANSMITTER



## (57) Abstract

A laser small arms transmitter (SAT) which may be affixed to the stock of a rifle such as an M16 used by a soldier in training with a multiple integrated laser engagement system (MILES). The transmitter includes a housing assembly having a forward end with a window through which the beam of a laser diode is emitted. A pair of optical wedges are positioned inside the housing assembly between the laser diode and the window. The optical wedges are supported for independent rotation about a common optical axis for steering the laser beam. An alignment head may be physically mated to the rearward end of the housing assembly for driving a pair of shafts to rotate the optical wedges in the alignment of the transmitter so that a soldier can accurately hit a target once he or she has located the target in the conventional sights of the rifle. The laser transmitter may also include a sensor for detecting the firing of a blank cartridge, a fire LED mounted inside the housing for producing an optical signal to indicate to the alignment head that the laser diode has been energized, and an inductive switch connected to a power circuit and actuable by an induction coil in the alignment head to energize the laser diode.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

DESCRIPTION  
LASER SMALL ARMS TRANSMITTER

TECHNICAL FIELD

The present invention relates to military training equipment, and more  
5 particularly, to a laser transmitter mounted on a rifle for use by a soldier in war  
games.

BACKGROUND ART

For many years the armed services of the United States have trained  
soldiers with a multiple integrated laser engagement system (MILES). A laser  
10 small arms transmitter (SAT) is affixed to the stock of a rifle such as an M16.  
Each soldier carries detectors on his helmet and on a body harness adapted to  
detect a laser "bullet" hit. The soldier pulls the trigger of his or her rifle to fire  
a blank to simulate the firing of an actual round and an audio sensor triggers the  
SAT.

15 It is necessary to align the SAT so that the soldier can accurately hit the  
target once he or she has it located in the conventional rifle sights. In the past an  
early version of the SAT was bolted to the rifle stock and the mechanical sights  
of the weapon were adjusted to align with the laser beam. The disadvantage of  
this approach is that the mechanical weapon sights must be readjusted in order to  
20 use the rifle with live rounds. To overcome this disadvantage the conventional  
SAT now in use incorporates mechanical linkages for changing the orientation of  
the laser.

The prior art small arms alignment fixture (SAAF) used by the U.S. Army  
for alignment of the conventional MILES SAT consists of a complex array of one  
25 hundred forty-four detectors which are used in conjunction with thirty-five printed  
circuit boards to determine where the laser hits with respect to a target reticle.

The difficulty in using the prior art SAAF is that the soldier aims his or her weapon at the array which is twenty-five meters away without the use of a stable platform. In many cases, the soldier fires his or her weapon in a manner which results in the aim point not being at the desired location. The fact that the array  
5 is located twenty-five meters away from the soldier introduces visibility limitations due to snow, fog, wind and poor lighting conditions at sunrise or dusk.

The prior art SAAF calculates the number of error "clicks" in both azimuth and elevation. The number of clicks is then displayed on the prior art SAAF using four sets of electro-mechanical display indicators. The soldier must then turn his  
10 conventional SAT's adjustors the corresponding number of clicks in the correct direction. He or she must then aim and fire the weapon again and make additional corresponding adjustments. This iterative process continues until the soldier obtains a zero indication on the prior art SAAF. This is a very time consuming and tedious process due to normal aiming errors incurred each time the soldier has  
15 to reacquire the target reticle. It is not uncommon for a soldier to take fifteen minutes to align his or her weapon to the best of his or her ability and still not have it accurately aligned.

Not only is the alignment process utilizing the prior art SAAF time consuming, it also expensive because a large amount of blank ammunition must  
20 be used. The laser of a conventional SAT will not fire without a blank cartridge being ignited or by using a special dry fire trigger cable. The prior art SAAF does not support optical sights, different small arms weapon types, nor night vision devices. Nor does the prior art SAAF accurately verify the laser beam energy and encoding of the received laser beam.

25 It would therefore be desirable to provide an improved SAT which would eliminate the need to utilize a large target array. Such a SAT would also preferably be automatically adjustable for more rapid and accurate alignment. In addition, preferably the laser output of the improved SAT could have different

powers and codings to enable the manworn portion of a MILES system to discriminate between hits made by different small arms.

#### DISCLOSURE OF INVENTION

Accordingly, it is the primary object of the present invention to provide an  
5 improved laser small arms transmitter for use in a multiple integrated laser engagement system.

The present invention provides a laser transmitter that can be mounted to a small arms weapon. The laser transmitter has a laser energizable to emit a laser beam generally along the aim of the weapon. An alignment head of an electro-  
10 mechanical alignment system is connectable to the laser transmitter for adjusting the transmitter to steer the laser beam in azimuth and elevation until the laser beam is substantially aligned with a boresight of the weapon.

#### BRIEF DESCRIPTION OF DRAWING

The objects, advantages and features of this invention will be more readily  
15 appreciated from the following detailed description, when read in conjunction with the accompanying drawing, in which:

Fig. 1A is a perspective view of a soldier aiming his or her rifle in an automatic player identification small arms laser alignment system.

Fig. 1B is a side elevation view of the alignment system of Fig. 1A with  
20 portions broken away to reveal further details.

Fig. 2 is an enlarged front elevation view of the display panel and switches of the control unit of the alignment system of Fig. 1A and 1B.

Fig. 3 is an enlarged exploded perspective view of a preferred embodiment of our small arms transmitter (SAT) which is mounted on the rifle shown in Fig.  
25 1A and 1B.

Fig. 4 is a diagrammatic illustration of laser beamsteering using optical wedges.

Fig. 5A and 5B are side and front elevation views of the alignment head of the alignment system of Figs. 1A and 1B.

5 Fig. 6 is a diagrammatic illustration of the lens, beam splitter, target reticle and position sensor detector of the optics unit of the alignment system of Fig. 1A and 1B.

Fig. 7 is an overall block diagram of the alignment system of Fig. 1A and 1B.

10 Fig. 8 is a block diagram of the optical output power and code accuracy verification circuit of the control unit of the alignment system of Fig. 1A and 1B.

#### BEST MODES FOR CARRYING OUT THE INVENTION

Referring to Fig. 1A and 1B, the preferred embodiment of our invention is illustrated in the form of a laser small arms transmitter (SAT) 12 bolted to the stock of a small arms weapon 14 such as an M16 rifle for subsequent use by a  
15 soldier in war games. Our SAT 12 is designed to be automatically adjusted by an alignment system 10 which includes a rectangular hollow transit case 16 which is horizontally oriented when in use. A lockable hinged end cover 18 of the case 16 may be swung upwardly to reveal a control unit 20 mounted to the inside thereof.  
20 A soldier 21 aims the weapon 14 inside the case 16. The soldier 21 wears a helmet 21a and a harness 21b equipped with laser detectors which detect laser "bullet" hits in subsequent war games. The control unit 20 includes a box-like housing 22 (Fig. 2) having an LCD display 24. The housing 22 also has a keypad in the form of a membrane switch panel. This switch panel surrounds the display  
25 24 and includes pressure-type switches 26, 28, 30, 32, 34, 36 and 38.

A retractable sliding rack 40 may be extended horizontally from the rear end of a base unit 42 (Fig. 1B) mounted to the bottom wall of the case 16. A

barrel 44 of the rifle 14 is firmly supported on the apex of a rigid triangular weapon rest 46 whose base is securely mounted via bolts to an intermediate portion of the base unit 42. A trigger guard (not visible) of the rifle 14 is mounted in a vise 48 on the rack 40. The vise 48 has knobs 50 and 52 for manually  
5 adjusting the azimuth and elevation, respectively, of the barrel 44 of the rifle 14. After mounting the rifle 14 on the weapon rest 46 and vise 48, the soldier 21 (Fig. 1A) aims at an image of a target reticle 54 (Fig. 6) projected in the line of sight of the weapon as hereafter described in detail.

A box-shaped optics unit 56 (Figs. 1A and 1B) is rigidly mounted on the  
10 forward portion of the base unit 42 (Fig. 1B). The optics unit 56 includes a convex lens 58 (Fig. 6) and a beam splitter 60. The beam splitter 60 is transparent to infrared light from the SAT 12 but reflective to visible light. The target reticle 54 (Fig. 6) is mounted inside the optics unit 56 below the axis of the laser beam. The beam splitter 60 is positioned forward of the lens 58 and is angled at forty-five  
15 degrees to project the image V of the target reticle through the lens 58 at infinity. A position sensor detector 62 in the optics unit 56 receives the laser beam L2 and generates an error signal representative of a displacement between a received location of the laser beam and the image of the target reticle. The SAT 12 is then adjusted until its laser beam L2 strikes the center of the detector 62.

20 A control circuit inside the control unit 20 (Fig. 1) is connected to an alignment head 64 which is mechanically coupled with a rear end of the SAT 12 bolted to the rifle 14. The control circuit causes the alignment head 64 to repetitively trigger the laser in the SAT 12. Utilizing the error signal, the control circuit causes the alignment head to independently rotate a pair of wedge prisms  
25 66 and 68 (Fig. 3), each including a surrounding spur gear, in the SAT 12 to steer the laser beam in azimuth and elevation until the laser beam is substantially aligned with a boresight of the barrel 44 of the weapon.

The alignment system 10 may be used for the automatic boresight alignment of all U.S. military specified small arm weapons and machine guns with unlimited adaptability to new weapons. The automatic operation of the system assures rapid (less than one minute), accurate and consistent boresighting of the SAT 12 after a single initial sighting of the weapon 14 by the soldier 21. Use of the sighting vise 48 assures that optical sights and night vision devices on the weapon 14 will not interfere with the boresighting process. The entire alignment system 10 is contained within the rugged transit case 16 which also serves as a sun and foul weather shield. The alignment system 10 does not use blank ammunition during the alignment process and therefore it may be used at any location such as indoors on a table top. The initial set up of the alignment system 10 involves three simple steps which include installation of battery into the control unit housing 22 (Fig. 1), activating the BIT switch 30 (Fig. 2) and selecting the weapon type to be aligned by depressing the switch 34. The display 24 will give appropriate text messages and directions to the operator as to how to proceed to the next step. Once the alignment system 10 is ready for alignment the soldier 21 follows the directions on the display 24 to align his or her weapon. The typical sequence is as follows:

- a) The soldier attaches the alignment head 64 to the laser small arms transmitter (SAT) 12;
- b) The soldier places his or her weapon in the sight vise 48 and front weapon rest 46;
- c) The soldier aims his or her weapon at the image of the illuminated target reticle 54 visible in the optics unit using the sighting vise azimuth and elevation adjustment knobs 50 and 52;
- d) The soldier depresses the proceed switch 28 (Fig. 2) and follows the instructions on the display 24. The weapon type is selected by



depressing the switch 34 at the appropriate time in response to a query on the display;

e) The soldier backs away and depresses the align switch 26 on the control unit housing 22;

5 f) The soldier waits for an "ALIGNMENT COMPLETE" message on the display 24 which will occur less than one minute later; and

g) The soldier removes the weapon from the alignment system following an alignment completion instruction.

In the event any problems are encountered by the alignment system 10  
10 during the alignment process such as low power, incorrect laser coding or triggering problems, the system will inform the soldier that the weapon's SAT 12 is defective and needs to be replaced.

The overall operation of the alignment system 10 is illustrated in the block diagram of Fig. 7. The weapon 14 is mounted in the sight vise 48 with the  
15 alignment head 64 attached to the SAT 12. The optics unit 56 includes the illuminated target reticle 54 at which the weapon's sights are aimed. When the align switch 26 (Fig. 2) is activated the control unit 20 causes the SAT 12 to be repetitively triggered while monitoring the SAT's fire LEID (not illustrated) mounted behind a window 70 (Fig. 3) indicator for proper operation. The optics  
20 unit 20 senses the location of the laser and sends that data to the control unit 20 which in turn determines the amount of correction needed. The control unit 20 in turn causes the alignment head 64 to make the necessary adjustments to the SAT 12. The process continues in real time until the SAT 12 is precisely aligned. The control unit 20, in conjunction with the optics unit 56, also checks for laser power  
25 levels, laser codes and that the SAT's alignment optics are performing as desired. The five major sub-assemblies of the alignment system 10 are discussed in further detail hereafter.

nt covering for the hole may  
ate the laser beam, or deflect  
an electromechanical device  
1A) and automatically adjusts  
unit 20. The alignment head  
used to trigger the SAT's laser  
a testing player identification  
80 which monitors the SAT's  
vo miniature reduction geared  
t gear trains 86 and 87 within  
upplings (not visible) on a pair  
over the ends of the SAT's  
d motors 82 and 84 are driven  
boresighting process while the  
les real time feedback to the

2 (Fig. 3) includes a housing  
which forms a rear end thereof.  
e housing assembly 88 and is  
d 94 also mounted within the  
ted to energize the laser diode  
to the inside of the rear cover  
y energization of the induction  
housing assembly 88 (Fig. 3) in

nably 88 (Fig. 3) is formed with  
not illustrated) for detecting the

it 56 (Figs. 1B) is the assembly which projects the illuminated  
e soldier 21 during boresighting and senses the location of the  
with respect to the reticle. The illuminated reticle 54 assists  
esighting during reduced lighting conditions such as dusk or  
ates the operation of the principal components of the optics  
large convex lens 58 serves the function of collimating and  
am to a spot at the longitudinal position sensor detector 62  
e focal point of the lens 58. When the angle of incidence to  
r beam is not perpendicular (mis-aligned) the position of the  
2 is offset. The detector 62 passively quantifies the amount  
e error to the control unit 20. The detector is preferably a  
h as a quad-detector or it may be a linear detector with an  
the path of the laser beam is the beam splitter 60 which is  
ght while allowing the infrared light from the laser to pass  
e beam splitter 60 is supported at a forty-five degree angle  
the target reticle 54 through the same lens as the incoming  
get reticle 54 is illuminated by a visible light source such  
positioned such that the projected image is on the same  
ro point of the position sensor detector 62. No field  
es unit 56 are required and the system 10 need not contain  
than the detector 62 and the LED light source 72 for  
reticle 54.

roductive barrier 74 (Fig. 1) is rigidly secured via bolts to the  
e tip of the barrel 44 of the weapon and the optics unit 56.  
rom inadvertently striking the lens 58 of the optical unit  
mounting the rifle 14 on the weapon rest 46 and vise 48.  
erethrough covered by a metal screen 76 for allowing the  
be eight millimeters wide to pass through the same to the

beam. The angular radius of this cone is approximately  $\theta_d$ . Apex angle is controlled to within very tight tolerances in the manufacturing process of the wedges. As a result of the melt-to-melt index tolerance, deviation angles (functions of wave-length) are nominally specified.

5        The deviation angles are specified with the assumption that the input beam is *normal* to the perpendicular face. At other input angles the deviation will, of course, be different. To determine the deviation angle for the same input direction but other wavelengths, the equation is:  $\theta_d = \arcsin(n \sin \theta_w) - \theta_w$ , where  $\theta_d$  is the deviation angle,  $\theta_w$  is the wedge angle and  $n$  is the nominal index at the  
10       appropriate wavelength. Optical wedges are available in various materials, such as synthetic fused silica, and in different shapes and sizes.

      The control unit 20 (Fig. 1A) provides the user-friendly LCD display 24 (Fig. 2) and controls which continuously inform the user of his weapon status while progressively instructing him throughout the alignment process. The control  
15       unit 20 is mounted inside the transit case cover 18. The LCD display 24 can be easily read when the cover 18 is in raised open position. As described above the control unit 20 provides all controls and monitors all activities of the optics and alignment head units 56 and 64. The front membrane switch panel with its  
20       integral 4X20 LCD display 24 provides the user interface. The switch functions are described as follows:

- a) ALIGN (26) - This switch is activated by the soldier after he or she has aimed the weapon's sights at the optics units target reticle.
- b) PROCEED (28) - This switch is activated any time the soldier desires to move to the next alignment step or to acknowledge a  
25       displayed message.
- c) BIT (30) - This switch is activated during initial setup of the system to verify its ready status.

- 5 d) PID LEARN (32) - This switch is used to transfer the system's test PID to the SAT 12 in order to verify that the transfer function operators. Use of this switch is optional and is only used if there is some question as to the SAT of the cradled weapon being able to accept other PIDs.
- e) WEAPON SELECT (34) - This switch is used in conjunction with the two arrow switches 36 and 38 to select the type of weapon to be aligned (M16A2, M2, M240 etc.). This selection determines which power levels and codes are to be verified by the system.
- 10 f) ARROWS (36 and 38) - These switches are used to select the different weapon types.

The sighting vise 48 (Fig. 1B) is a stable mechanism used to hold and aim the weapon 14 under alignment. It allows the soldier to boresight using any aiming bias introduced by his method of aiming and eliminates any weapon wandering away from the aim point. The vise 48 is attached to the sliding rack 40 which retracts into the transit case base unit 42 to accommodate the different lengths of weapons. The sight vise 48 has both elevation and azimuth adjustment knobs 50 and 52 allowing the soldier to accurately aim his weapon's sights at the image of the target reticle 54. The front portion of the weapon barrel 44 rests on the weapon rest 46 located within the transit case 16 on the transit case base unit 42.

15  
20

The major components of the alignment system 10 are integral to the transit case 16 which provides a secure and rugged environment during transport and operation. The case 16 also provides a sun and foul weather shield to allow the alignment process to be accomplished in any expected environment. The base unit 42 is mounted on the bottom wall of the case. The optics unit 56, weapon rest 46 and sliding sight vise rack 40 are attached to the base unit battery (not

25

visible) for powering the system is housed inside the base unit 42. The control unit 20 is attached to the inside of the front cover 18A.

Fig. 8 is a block diagram of the optical output power and code accuracy verification circuit of the control unit 20. An encoding circuit 122 is connected  
5 via a serial data bus 124 to a microcomputer (not illustrated). An optical bit amplifier 126 in the path of the laser beam outputs signals to the encoding electronics.

While we have described a preferred embodiment of our laser small arms transmitter and its automatic adjustment by an alignment system, it will be  
10 apparent to those skilled in the art that our invention can be modified in both arrangement and detail. Therefore, the protection afforded our invention should only be limited in accordance with the following claims.

CLAIMS

1. A laser transmitter for mounting to a small arms weapon to simulate the firing of an actual round, comprising:
  - a housing assembly having a forward end with a window;
  - 5 a laser diode mounted inside the housing assembly for emitting a laser beam through the window;
  - a power circuit mounted in the housing assembly and connected to the laser diode for energizing the diode to cause it to emit the laser beam;
  - first and second optical wedges positioned between the laser diode and the
  - 10 window;
  - means for supporting the first and second optical wedges for independent rotation about a common optical axis for steering the laser beam; and
  - drive means connected to the optical wedge supporting means having portions extending through the housing assembly for coupling to an alignment
  - 15 head.
2. A laser transmitter according to Claim 1 wherein the optical wedges having substantially equal deviation.
3. A laser transmitter according to Claim 1 wherein each optical wedge has a first face perpendicular to the common optical axis and a second face which
- 20 extends at an angle relative to the common optical axis.
4. A laser transmitter according to Claim 3 wherein the first and second optical wedges are supported with their first perpendicular faces in near contact.

5. A laser transmitter according to Claim 1 wherein the means for supporting the first and second optical wedges includes first and second spur gears, each surrounding a corresponding one of the wedges.
6. A laser transmitter according to Claim 5 wherein the drive means  
5 includes first and second adjustment shafts and first and second pinion gears mounted on corresponding ones of the adjustment shafts for engaging corresponding ones of the spur gears, and the adjustment shafts having ends which extend through a corresponding one of a pair of holes in a rearward end of the housing assembly for driving connection to the alignment head.
- 10 7. A laser transmitter according to Claim 6 including a flange extending from the housing assembly adjacent the holes to protect the ends of the adjustment shafts which extend therethrough.
8. A laser transmitter according to Claim 1 wherein the rearward end  
15 of the housing assembly has a second window and a fire LED mounted behind the second window.
9. A laser transmitter according to Claim 1 wherein the transmitter further comprises a sensor for detecting the firing of a blank cartridge.
10. A laser transmitter according to Claim 1 wherein the transmitter  
20 further comprises an inductive switch connected to the power circuit and actuable by an induction coil in the alignment head to energize the laser diode.
11. A laser transmitter for mounting to a small arms weapon to simulate the firing of an actual round comprising:

a housing assembly having a forward end with a first window;  
a laser mounted inside the housing assembly for emitting a laser beam through the first window;  
a power circuit mounted inside the housing assembly and connected to the  
5 laser for energizing the laser to cause it to emit the laser beam;  
driveable means for steering the laser beam;  
means for driving the steering means; and  
an inductive switch connected to the power circuit and actuable by an  
induction coil in an alignment head mountable on the housing assembly to energize  
10 the laser.

12. A laser transmitter according to Claim 11 wherein the means for steering the laser beam includes first and second optical wedges positioned between the laser and the first window and means for supporting the first and second optical wedges for independent rotation by the driving means about a  
15 common axis.

13. A laser transmitter according to Claim 11 wherein the housing assembly has a rearward end with a second window and a fire LED is mounted behind the second window inside the housing assembly.

14. A laser transmitter according to Claim 11 wherein the housing  
20 assembly includes a hollow rectangular box and the rearward end of the housing assembly is a removable cover assembly.

15. A laser transmitter according to Claim 12 wherein the optical wedges each have a first face perpendicular to the common optical axis and a second face which extends at an angle relative to the common optical axis.



16. A laser transmitter according to Claim 15 wherein the first and second optical wedges are supported with their first perpendicular faces in near contact.

17. A laser transmitter according to Claim 12 wherein the means for supporting the first and second optical wedges include the first and second spur gears each surrounding a corresponding one of the wedges.

18. A laser transmitter according to Claim 17 wherein the driving means includes first and second adjustment shafts and first and second pinion gears mounted on corresponding ones of the adjustment shafts for engaging corresponding ones of the spur gears, the adjustment shafts having ends which extend through a rearward end of the housing assembly for driving connection to the alignment head.

19. A laser transmitter according to Claim 11 wherein the forward end of the housing assembly includes a second window and the transmitter further comprises a sensor mounted behind the second window for detecting the firing of a blank cartridge.

20. A laser transmitter for mounting to a small arms weapon to simulate the firing of an actual round comprising:  
a housing assembly having a forward end with a first window and a second window, and a rearward end with a third window;  
a laser diode mounted inside the housing assembly for emitting a laser beam through the first window;

a power circuit mounted in the housing assembly and connected to the laser diode for energizing the diode to cause it to emit the laser beam through the first window;

5 an inductive switch connected to the power circuit and actuable by an induction coil in an alignment head mountable to the housing assembly to energize the laser diode;

a sensor mounted inside the housing assembly behind the second window for detecting the firing of a blank cartridge;

10 a fire LED mounted inside the housing behind the third window for producing an optical signal to indicate to the alignment head that the laser diode has been energized;

first and second optical wedges positioned inside the housing assembly between the laser diode and the first window;

15 means for supporting the first and second optical wedges for independent rotation about a common optical axis for steering the laser beam; and

drive means connected to the optical wedge supporting means having portions extending through the rearward end of the housing assembly for coupling to the alignment head.




FIG. 1A

2/5





FIG. 1B

3/5

FIG. 3







FIG. 5A

FIG. 5B





FIG. 4

5/5




FIG. 6




FIG. 7




FIG. 8

# INTERNATIONAL SEARCH REPORT

Internat. Application No  
**PCT/US 95/05253**

**A. CLASSIFICATION OF SUBJECT MATTER**  
**IPC 6 F41A33/02**

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

**IPC 6 F41A F41G**

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US,A,4 488 369 (VAN NOTE) 18 December 1984  see column 2, line 48 - column 3, line 11; figures	1-4, 11-14,20
Y	EP,A,0 057 304 (EL-OP ELECTRO-OPTICS INDUSTRIES LIMITED) 11 August 1982 see column 7, line 9 - column 9, line 11; figures	1-4, 11-14,20
A	MANUFACTURING TECHNOLOGY NOTE, September 1979 VIRGINIA, 'Laser Simulator for Rifle Fire'	1,11,20

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*&\* document member of the same patent family

Date of the actual completion of the international search

**26 September 1995**

Date of mailing of the international search report

**04. 10. 95**

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,  
Fax (+ 31-70) 340-3016

Authorized officer

**Olsson, B**



# INTERNATIONAL SEARCH REPORT

Internat I Application No

PCT/US 95/05253

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A-4488369	18-12-84	NONE	
EP-A-57304	11-08-82	NONE	



**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**